

BOILER COMPLETE TREAT "S" is a multi-functional formula with all the necessary chemicals for a complete boiler treatment in one convenient liquid. It combines hardness control with oxygen scavengers and a volatile amine corrosion inhibitor that travels with the steam to protect steam and condensate plumbing.

APPLICATION:

The dosage of BOILER COMPLETE TREAT "S" will depend on the percent of condensate returned, makeup water characteristics and initial cleanliness of heat transfer surfaces. The treatment program must be accompanied by a program of regular blowdown to remove sludge and suspended solids from the boiler.

BOILER COMPLETE TREAT "S" may be fed on a "one-shot" basis or with an automated continuous system. Gradual and continuous feeding is recommended for industrial process and other large boilers. BOILER COMPLETE TREAT "S" may be mixed with other boiler treatment chemicals and diluted with water for convenient feeding. If the boiler water system has not been previously treated, add a starting dose of twice the amount recommended for weekly maintenance for the first four weeks.

For weekly maintenance: Add 1/2 gallon (2 quarts) of BOILER COMPLETE TREAT "S" per week for each 25 horsepower of boiler capacity. This use rate may vary due to feedwater hardness and differences in a boilers rated horsepower versus the boilers operational horsepower. Control the level of BOILER COMPLETE TREAT "S" by maintaining a hydroxide (OH) alkalinity level between 150 - 250 ppm and sulfite levels of between 20-40 ppm.

BOILER COMPLETE TREAT "S"

SUPERIOR PROTECTION IN
SOFT WATER SYSTEMS

CONTAINS OXYGEN SCAVENGER
AND STEAM LINE TREATMENT

WARNING:

Harmful if swallowed. May cause severe burns. See back panel for further precautions and first aid instructions.

KEEP OUT OF REACH OF CHILDREN

Sold By:

SPECIMEN LABEL

Blowdown: Open the blowdown valve until the level drop in the sight glass is reached, recommended starting point is 2 inches twice per week. Blowdown schedules will vary depending upon water hardness and permissible cycles of concentration.

WARNING:

Harmful if swallowed. May cause severe burns. Do not take internally. Avoid contact with eyes, skin and mucous membranes.

FIRST AID:

If Swallowed: Give person several glasses of water. DO NOT induce vomiting. Obtain immediate medical assistance.

If In Eyes: Flush with plenty of cool water for at least 15 minutes. Obtain immediate medical assistance.

If On Skin: Wash thoroughly with soap and water. If irritation persists, obtain medical assistance.

KEEP OUT OF REACH OF CHILDREN

This Product Contains	CAS No.
Water	7732-18-5
Polyacrylate Scale Inhibitor	No CAS Number
Potassium Hydroxide	1310-58-3
Diethylethanolamine	100-37-8
Tetrapotassium Pyrophosphate	7320-34-5

196092809

NET CONTENTS:

5 6 20 30 35 55
GALLONS