

# MATERIAL SAFETY DATA SHEET



Bio Chem, Inc.  
P.O. Box 521925  
SLC, UT84152 - USA

GENERAL INFORMATION NUMBER: 1-800-653-9795

REVISION DATE: February 25, 2002  
DATE OF ISSUE: February 25, 2002

5/1/90

10-99 ACRYLIC LATEX LIQUID - #20-55 FLAT WALLCOATING  
#20-66 ACRYLIC LATEX SEALER - #21-22 LINE MARKING PAINT

## SECTION II: HAZARDOUS INGREDIENTS

INGREDIENT	NTP/ IARC/ OSHA CARC.	PERCENT	OSHA PEL (PPM)	NIOSH CEILING (PPM)	ACGIH TLV (PPM)	LEL PERCENT	VAPOR PRESSURE
Oxazolidene Family Amine CAS #97553-90-7	No	0.1-0.2	3	N.A.	N.A.	N.A.	6 mm/Hg

This amine is classified as a formaldehyde donor, which is listed as carcinogen.

N.A. = Not Applicable/Not Applicable

## SECTION III: PHYSICAL DATA

BOILING RANGE 212°F VAPOR DENSITY  HEAVIER  LIGHTER. THAN AIR  
EVAPORATION RATE  FASTER  SLOWER. THAN ETHER PERCENT VOLATILE BY VOLUME 45-85 WEIGHT PER GALLON 8.5-11.3 Lbs.

APPEARANCE & ODOR: Milky liquid with slight ammoniacal odor.

## SECTION IV: FIRE AND EXPLOSION DATA

DOT Category: Not Regulated Flash Point: N.A. LEL: N.A.

Extinguishing Media: N.A.

Special Firefighting Procedures: N.A.

Unusual Fire & Explosion Hazards: N.A.

Hazardous Decomposition Products: May form toxic materials - carbon monoxide, carbon dioxide and nitrogen oxides.

Target Organ Information: Overexposure may cause damage to skin and respiratory system.

Reportable Spill Information: Not reportable to the National Response Center.

SEE OTHER SIDE